


New Products



Available soon



Available soon



Available soon



Available soon

I-87015 / I-87015-G (Gray color)

7-channel RTD Input Module

- ▶ Analog Input channels : 7
- ▶ Input Type : Pt100,Pt1000, Ni120, Cu100, Cu1000 supports 2/3 wire RTD
- ▶ Accuracy : +/-0.05%
- ▶ Sampling Rate : 10 samples/second (Total)
- ▶ Common Mode Rejection : Typical 86dB
- ▶ Voltage Input Impedance : >1M Ohms
- ▶ Isolation Voltage : 3000Vrms
- ▶ Channels configurable for different types of input individually
- ▶ Wire Opening Detection
- ▶ Power consumption :1.0W

I-87015T / I-87015T-G(Gray color)

8-channel Thermistor Input Module

- ▶ Analog Input channels : 8
- ▶ Input Type :Precon ST-A3, Type u Fenwell
- ▶ Accuracy : +/-0.1%
- ▶ Sampling Rate : 8 samples/second (Total)
- ▶ Common Mode Rejection : Typical 86dB
- ▶ Voltage Input Impedance : >1M Ohms
- ▶ Isolation Voltage : 3000Vrms
- ▶ Channels configurable for different types of input individually
- ▶ Wire Opening Detection
- ▶ Power consumption :1.0W

I-87019 / I-87019-G (Gray color)

8-channel Universal Analog Input Module

- ▶ Input Type : mV, V, mA, Thermocouple
- ▶ Sampling Rate : 8 samples/second (Total)
- ▶ -3dB BandWidth : 15.7Hz
- ▶ Accuracy : +/-0.1%
- ▶ Common Mode Rejection : Typical 86dB
- ▶ Voltage Input Impedance : 1M Ohms
- ▶ Overvoltage Protection : +/-240Vrms
- ▶ Isolation Voltage : 3000Vrms
- ▶ Channels configurable for different types of input individually
- ▶ Wire Opening Detection
- ▶ Power consumption :1.1W

I-7015T / I-7015T-G(Gray color)

8-channel Thermistor Input and 6-channel Digital Output Module

- ▶ Analog Input channels : 8
- ▶ Input Type :Precon ST-A3, Type u Fenwell
- ▶ Accuracy : +/-0.1%
- ▶ Sampling Rate : 8 samples/second (Total)
- ▶ Common Mode Rejection : Typical 86dB
- ▶ Voltage Input Impedance : >1M Ohms
- ▶ Alarm Output:6
Open Collector to 30V, 100mA, load (per channel)
- ▶ Isolation Voltage : 3000Vrms
- ▶ Channels configurable for different types of input individually
- ▶ Wire Opening Detection
- ▶ Power consumption :1.1W

Your Local Distributor


ICP CON



Vol.6.1

Intel Strong ARM,Windows CE Embedded controller

WinCon-8000=PC+PLC



Vol.6.1



SCADA software
Soft PLC
OPC.OCX

CE Approved
www.icpdas.com