



Introduction

The M-7000 series is a family of network data acquisition and control modules that support Modbus RTU and DCON protocols. With the Modbus RTU protocol, it can easily communicate with most popular SCADA/ HMI software and PLC. It has the same form factor as the I-7000 series.

Features

- 3000 VDC isolation (inter-module)
- High voltage overload protection: M-7017R, M-7018R, M-7019R, M-7055
- High digital input voltage, 50 Vdc: M-7055
- Short circuit protection for digital output: M-7055
- Open thermocouple detection: M-7018R, M-7019R
- Open RTD detection: M-7015, M-7033
- Individual channel configurable: M-7015, M-7019R

M-7000 *Analog Input Modules Selection Guide*

SERIES

Analog Input Modules Selection Guide

Module		M-7005	M-7015	M-7033 M-7033D
Analog Input	Resolution	16 bit	16 bit	16 bit
	Input channel	8 diff.	6 diff.	3 diff.
	Sampling rate	8Hz	12Hz	10Hz
	Voltage input	-	-	-
	Current input	-	-	-
	Sensor input	Thermistor (2 wire)	Pt/Ni/Cu RTD (2/3 wire)	Pt Ni-RTD (2/3/4 wire)
	4 1/2 digit LED Display	-	-	Yes for M-7033D
	Isolated loop power	-	-	-
	Input Linear scaling	-	-	-
	Isolation Voltage	3000V	3000V	3000V
Digital Input & Digital Output	Digital input channels	-	-	-
	Digital output channels	6	-	-
	Event counter	-	-	-
	High/Low Alarm	Yes	-	-
Individual Channel Configurable		Yes	Yes	-
Dual Watchdog Timer		Yes	Yes	Yes
Frame Ground		Yes	Yes	-
Availability		Call	Yes	Yes

Analog Input Modules Selection Guide

Module		M-7016/ M-7016D	M-7017	M-7017R
Analog Input	Resolution	16 bit	16 bit	16/12 bit
	Input channel	2 diff.	8 diff.	8 diff.
	Sampling rate	2/10Hz	10Hz (total)	10/60Hz (total)
	Fast Mode (12bit)	–	–	Yes
	Voltage input	+/-15mV +/-50mV +/-100mV +/-500mV +/-1V +/-2.5V	+/-150mV +/-500mV +/-1V +/-5V +/-10V	+/-150mV +/-500mV +/-1V +/-5V +/-10V
	Current input	+/-20mA	+/-20mA	+/-20mA
	Sensor input	4-wire Strain gauge Input	–	–
	4 1/2 digit LED Display	Yes for M-7016D	–	–
	Input Linear scaling	Yes	–	–
	Isolation Voltage	3000V	3000V	3000V
Digital Input & Digital Output	Digital input channels	1	–	–
	Digital output channels	4	–	–
	Event counter	Yes	–	–
	High/Low Alarm	Yes	–	–
Dual Watchdog Timer	Yes	Yes	Yes	
Over voltage protection	–	+/-35V	240Vrms	
Frame Ground	–	Yes	Yes	
Availability	Yes	Yes	Yes	

M-7000 *Analog Input Modules Selection Guide*

SERIES

Analog Input Modules Selection Guide

Module		M-7018	M-7018R	M-7019R
Analog Input	Resolution	16 bit	16 bit	16 bit
	Input channel	8 diff.	8 diff.	8 diff.
	Sampling rate	10Hz (total)	10Hz (total)	8Hz (total)
	Voltage input	+/-15mV +/-50mV +/-100mV +/-500mV +/-1V +/-2.5V	+/-15mV +/-50mV +/-100mV +/-500mV +/-1V +/-2.5V	+/-15mV +/-50mV +/-100mV +/-150mV +/-500mV +/-1V +/-2.5V +/-5V +/-10V
	Current input	+/-20mA	+/-20mA	+/-20mA
	Sensor input	J.K.T.E.R.S.B N.C. thermocouple	J.K.T.E.R.S.B N.C.L.M. thermocouple	J.K.T.E.R.S.B N.C.L.M.L2 (DIN43710) thermocouple
	4 1/2 digit LED Display	-	-	-
	Isolation Voltage	3000V	3000V	3000V
Break Line Detection	-	Yes	Yes	
Individual Channel Configurable	-	-	Yes	
Dual Watchdog Timer	Yes	Yes	Yes	
Over voltage protection	+/-35V	240Vrms	240Vrms	
Frame Ground	Yes	Yes	Yes	
Availability	Yes	Yes	Yes	

Analog Output Module Selection Guide

Module		M-7022	M-7024
Analog Output	Resolution	12 bit	14 bit
	Output Channels	2(*1)	4
	Voltage Output	0-10V	+/-10V, 0-10V +/-5V, 0-5V
	Current Output	0-20mA 4-20mA	0-20mA 4-20mA
Safe Value (When Host Fail or communication fail)		Yes	Yes
Power-on Preset Value		Yes	Yes
Dual Watchdog Timer		Yes	Yes
Availability		Yes	Yes

* 1: channel to channel isolation

M-7000 *Digital I/O Modules Selection Guide*

SERIES

Digital I/O, Relay and Counter Selection Guide

Module		M-7041/ M-7041D	M-7045/ M-7045D	M-7050/ M-7050D	M-7051/ M-7051D
Digital input and Digital output	Digital input channels	14 Isolation (3750V)	–	7	16 Isolation (3750V)
	Digital output channels (open collector)	–	16 Isolation (3750V)	8	–
	Alarm Setting	–	–	–	–
Counter	Channels	14	–	7	16
	Input frequency	100Hz	–	100Hz	100Hz
LED Display		Yes for M-7041D	Yes for M-7045D	Yes for M-7050D	Yes for M-7051D
Safe Value (When Host Fail or communication fail)		–	Yes	Yes	–
Power-on Preset Value		–	Yes	Yes	–
Dual Watchdog Timer		Yes	Yes	Yes	Yes
Availability		Yes	Yes	Yes	Yes

Digital I/O, Relay and Counter Selection Guide

Module		M-7052/ M-7052D	M-7053/ M-7053D	M-7055/ M-7055D
Digital input and Digital output	Digital input channels	8 Isolation (5000V)	16	8 Isolation (3750V)
	Digital output channels (open collector)	–	–	8 Isolation (3750V)
	Alarm Setting	–	–	–
Counter	Channels	8	16	8
	Input frequency	100Hz	100Hz	100Hz
LED Display		Yes for M-7052D	Yes for M-7053D	Yes for M-7055D
Safe Value (When Host Fail or communication fail)		–	–	Yes
Power-on Preset Value		–	–	Yes
Dual Watchdog Timer		Yes	Yes	Yes
Availability		Yes	Yes	Yes

M-7000

Digital I/O Modules Selection Guide

SERIES

M-7000

Digital I/O, Relay and Counter Selection Guide

Module		M-7060/ M-7060D	M-7067/ M-7067D	M-7080/ M-7080D
Digital input and Digital output	Digital input channels	4 Isolation (3750V)	–	–
	Digital output channels	4 Channel Relay Form A x 2 Form C x 2	7 Channel Relay Form A	2 Channel
	Alarm Setting	–	–	–
Counter	Channels	4	–	2
	Input frequency	100Hz	–	100 KHz
LED Display		Yes for M-7060D	Yes for M-7067D	Yes for M-7080D
Safe Value (When Host Fail or communication fail)		Yes	Yes	Yes
Power-on Preset Value		Yes	Yes	Yes
Dual Watchdog Timer		Yes	Yes	Yes
Availability		Yes	Yes	Yes

M-7000 Analog I/O Modules

SERIES

M-7005

**M-7005:****8-channel Thermistor Input and 6-channel Digital Output Module**

- Analog Input channels: 8
- Input Type: Precon ST-A3, Type u Fenwell, YSI, User-defined
- Accuracy: +/-0.1%
- Sampling Rate: 8 samples/second (Total)
- Common Mode Rejection: Typical 86dB
- Voltage Input Impedance: >1M Ohms
- Alarm Output: 6 Open Collector to 30V, 100mA, load (per channel)
- Isolation Voltage: 3000VDC
- Individual Channel Configurable
- Wire Opening Detection
- Power consumption: 1.1W

M-7015

**M-7015:****6-channel 3 wire RTD Input Module**

- Analog input types: Pt, Ni or Cu RTD
- Sampling rate: 12 samples/sec
- Accuracy: 0.05%
- Input Connection: 2 or 3 wires
- Individual channel configurable
- Wire Opening Detection

M-7016

M-7016D

**M-7016/7016D:****Strain Gauge Input Module**

- Resolution: 16 bit
- Channels: 2 channel
- Input type: mV, V and mA
- Input range: +/-15mV, +/-50mV, +/-100mV, +/-500mV, +/-1V, +/-2.5V, +/-20mA
- Isolation: 3000V
- Sampling rate: 10Hz for 1 channel mode
2Hz for 2 channel mode

M-7017

**M-7017:****8-channel Analog Input Module**

- Input Channels: 6 differential and 2 single-ended or 8 differential (jumper selectable)
- Input Types: mV, V, mA (requires optional external 125 ohms resistor)
- Input Ranges: +/-150mV, +/-500mV, +/-1V, +/-5V, +/-10V, +/-20mA
- Sampling Rate: 10 samples/sec total

M-7000 Analog I/O Modules

SERIES

M-7017R



M-7017R:

8-channel Analog Input Module

- Input Channels: 8 differential
- Over Voltage Protection: +/-240VRMS
- Sampling Rate: 10/60 samples/sec total
- Other Spec. is the same as M-7017

M-7018:

8-channel Thermocouple Input Module

- Input Channels: 6 differential and 2 single-ended or 8 differential (jumper selectable)
- Input Types: mV, V, mA (requires optional external 125 ohms resistor), Thermocouple
- Input Ranges: +/-15mV, +/-50mV, +/-100mV, +/-500mV, +/-1V, +/-2.5V, +/-20mA
- Thermocouple Types: J, K, T, E, R, S, B, N, C
- Sampling Rate: 10 samples/sec total

M-7018



M-7018R



M-7018R:

8-channel Thermocouple Input Module

- Input Channels: 8 differential
- Over Voltage Protection: +/-240VRMS
- Other Spec. is the same as M-7018

M-7019R:

8-channel Universal Analog Input Module

- Input Channels: 8 differential
- Input Types: mV, V, mA (jumper selectable), Thermocouple
- Input Ranges: +/-15mV, +/-50mV, +/-100mV, +/-150mV, +/-500mV, +/-1V, +/-2.5V, +/-5V, +/-10V, +/-20mA
- Thermocouple Types: J, K, T, E, R, S, B, N, C, L, M, L2
- Sampling Rate: 8 samples/sec total
- Accuracy: +/-0.1%
- Over Voltage Protection: +/-240VRMS
- Isolation Voltage: 3000 VDC

M-7019R



M-7000 Analog I/O Modules

SERIES

M-7022

**M-7022:****2-channel Analog Output Module**

- Resolution: 12 bit
- Analog output channel: 2
- Current output: 0-20mA, 4-20mA
- Voltage output: 0-10V
- Channel to channel isolated
- Programmable output slew rate
0.0625 to 512 V/sec
0.125 to 1024 mA/sec

M-7024

**M-7024:****4-channel Analog Output Module**

- Resolution: 14 bit
- Current output 0-20mA, 4-20mA
- Voltage output: +/-10V, 0-10V, +/-5V, 0-5V
- Programmable output slew rate
0.0625 to 1024V/sec
0.125 to 2048 mA/sec

M-7033

M-7033D

**M-7033:****3-channel RTD Input Module****M-7033D:****M-7033 with LED Display**

- Sampling rate: 15Hz (Total)
- Analog input type: Pt, Ni RTD
- Input Channel: 3 diff
- Input Connection: 2,3 or 4 wire
- Pt 100 input range:
+/-100°C, 0~100°C, 0~200°C, 0~600°C
- Ni 120 input range:
-80~100°C, 0~100°C

M-7000 Digital I/O Modules

SERIES

M-7041 M-7041D



M-7041: Isolated Digital Input Module
M-7041D: M-7041 with LED Display

- Input: 14 single-ended
 ON Voltage Level: 4V to 30V.
 OFF Voltage Level: 0 to 1V.
- Isolation voltage: 3750V rms
- Input resistance: 3K Ohms, 1/4W

M-7045 M-7045D



M-7045: 16 channel Isolated Digital Output Module
M-7045D: M-7045 with LED Display

- Channels : 16
- External Voltage : 10 to 40V max.
- Output current : 650mA per channel
- Isolation Voltage : 3750Vrms
- Direct drive power relay module
- Power consumption: 0.5W
- Short circuit protection

M-7050 M-7050D



M-7050: Non-isolated Digital I/O Module
M-7050D: M-7050 with LED Display

- Digital input channels: 7
 Level:
 ON Voltage Level: +3.5 ~ +30V
 OFF Voltage Level: +1V max.
- Digital output channels: 8
 Open collector to 30V, 30mA max. load
 Power dissipation: 300mW

M-7051 M-7051D



M-7051: Isolated Digital Input Module
M-7051D: M-7051 with LED Display

- Digital Input Channels: 16
- Isolation voltage: 3750 Vrms
- Digital input status:
 Dry contact:
 ON Voltage Level: close to GND
 OFF Voltage Level: open
 Wet contact:
 ON Voltage Level: +10V to +50V
 OFF Voltage Level: +3V max
 Effective distance for dry contact:
 500m max

M-7052 M-7052D



M-7052: Isolated Digital Input Module
M-7052D: M-7052 with LED Display

- Input: 6 differential and 2 single-ended
 ON Voltage Level: 3.5V to 30V.
 OFF Voltage Level: 0 to 1V.
- Isolation voltage: 5000V rms
- Input resistance: 3K Ohms, 1/4W

M-7000 Digital I/O Modules

SERIES

M-7053



M-7053D



M-7053: Non-isolated Digital Input Module
M-7053D: M-7053 with Display

- Input: 16 single-ended
- ON Voltage Level: 4V to 30V.
- OFF Voltage Level: 0 to 2V.

M-7055



M-7055D



M-7055: Isolated Digital Input Module
M-7055D: M-7055 LED Display

- Digital Input Channels: 8
- Digital Input status
- Dry contact: ON Voltage Level: close to GND
- OFF Voltage Level: open
- Wet contact: ON Voltage Level: +10V to +50V
- OFF Voltage Level: +3V max
- Effective distance for dry contact: 500m max
- Digital Output channels: 8
- Open collector to 40V, 650mA max. load (Short Circuit Protection)
- Optical Isolation: 3750VDC

M-7060



M-7060D



M-7060: Relay Output & Isolated Digital Input Module
M-7060D: M-7060 with LED Display

- Input: 4 single-ended
- ON Voltage Level: 4V to 30V.
- OFF Voltage Level: 0 to 1V.
- Isolation voltage: 3750V rms
- Input resistance: 3K Ohms, 1/4W
- Output: 4-channel relay

M-7067



M-7067D



M-7067: Relay Output Module
M-7067D: M-7067 with Display

- Relay output: 7 Form A
- Contact rating: AC: 125V @0.5A
- DC: 24V @2A

Counter Modules

M-7080



M-7080D



M-7080: Counter/Frequency Input Module
M-7080D: M-7080 with LED Display

- Counter input: 2 independent 32 bit counter
- Frequency input: 100K Hz max
- Input: 3750V isolated or non-isolated
- Non-isolated programmable threshold value
- Programmable digital noise filter
- LED indicator: 5 digit readout (1-7080D)