

5.3. ZigBee I/O Modules

5

ZigBee Products



ZB-2015-T

Wireless 6-ch RTD Input Module
with 3-wire RTD Lead Resistance Elimination

Introduction

The ZB-2015-T offers 6 channels, each of which could be connected with different kinds of RTD. It features automatic compensation for 3-wire RTD with long-distance measurement so that it can measure right regardless of the length of wires. Also, ZB-2015-T is fully RoHS-compliant and has qualification for 4 kV ESD protection as well as 3000 Vdc intra-module isolation. Users can be easy to configure the module address, Protocol, Checksum, ZB-PID, ZB-ch and type code by rotary and DIP switch.

I/O Specifications

Analog Input	
Input Channel	6
Input Type	2/3-wire RTD
RTD Type	Pt100, Pt1000, Ni120, Cu100, Cu1000
Resolution	16-bit
Sampling Rate	12 Sample/Sec. (Total)
Accuracy	+/-0.05%
Zero Drift	+/-0.5 μ V/ $^{\circ}$ C
Span Drift	+/-20 μ V/ $^{\circ}$ C
Common Mode Rejection	150 dB
Normal Mode Rejection	100 dB
Open Wire Detection	Yes
Overvoltage Protection	120 Vdc/110 Vdc
Individual Channel Configurable	Yes
3-wire RTD Lead Resistance Elimination	Yes
ESD Protection	+/-4 kV contact for each channel and +/-8 kV Air for random point
Intra-module Isolated, Field to Logic	3000 Vdc

RTD Type Setting (TT)

Type Cod	RTD Type	Temperature Range
20	Platinum 100, $\alpha=0.00385$	-100 $^{\circ}$ C ~ +100 $^{\circ}$ C
21	Platinum 100, $\alpha=0.00385$	0 $^{\circ}$ C ~ +100 $^{\circ}$ C
22	Platinum 100, $\alpha=0.00385$	0 $^{\circ}$ C ~ +200 $^{\circ}$ C
23	Platinum 100, $\alpha=0.00385$	0 $^{\circ}$ C ~ +600 $^{\circ}$ C
24	Platinum 100, $\alpha=0.003916$	-100 $^{\circ}$ C ~ +100 $^{\circ}$ C
25	Platinum 100, $\alpha=0.003916$	0 $^{\circ}$ C ~ +100 $^{\circ}$ C
26	Platinum 100, $\alpha=0.003916$	0 $^{\circ}$ C ~ +200 $^{\circ}$ C
27	Platinum 100, $\alpha=0.003916$	0 $^{\circ}$ C ~ +600 $^{\circ}$ C

Features

- ISM 2.4 GHz Operating Frequency
- Fully Compliant 2.4 G IEEE802.15.4/ZigBee Specifications
- Wireless Transmission Range up to 700 m (ZB-2550P/ZB-2570P)
- Wireless Transmission Range up to 100 m (ZB-2550/ZB-2570)
- GUI Configuration Software (Windows Version)
- 3-wire RTD Input with Lead Resistance Elimination
- Individual Channel Configuration
- Open Wire Detection
- Overvoltage Protection
- DIN-Rail Mount



Applications

Building Automation, Factory Automation, Machine Automation, Remote Maintenance, Remote diagnosis, Testing Equipment.

System Specifications


Communication Interface	
Wireless	ZigBee, IEEE 802.15.4 Standard
Antenna	2.4 GHz-3 dBi Omni-Directional antenna
Protocols	Supports DCON and Modbus RTU Protocols
Hot Swap	By Rotary and DIP switch
LED Indicators	
Power	1 LED, red
ZigBee Communication	1 LED, green
Power	
Power Consumption	1.5 W max.
Mechanical	
Flammability	Fire Retardant Materials (UL94-V0 Level)
Dimensions (W x L x H)	33 mm x 87 mm x 107 mm
Installation	DIN-Rail
Environment	
Operating Temperature	-25 $^{\circ}$ C ~ +75 $^{\circ}$ C
Storage Temperature	-30 $^{\circ}$ C ~ +80 $^{\circ}$ C
Humidity	10 ~ 90% RH, non-condensing

3


ZigBee I/O Modules

ZB-2015-T


Wiring



Appearance



Dimensions (Unit: mm)



Ordering Information

ZB-2015-T CR	Wireless 6-ch RTD Input Module with 3-wire RTD Lead Resistance Elimination (RoHS)
Important Note: The ZigBee AIO modules need a ZB-2570 to coordinate the data transmission route, please remember to also order a ZB-2570 when you purchase the ZB DIO products.	

Accessories

MDR-20-24	24 Vdc/1.0 A, 24 W Power Supply with DIN-Rail Mounting
ZB-2510 CR	ZigBee Repeater (RoHS)
ZB-2510P CR	High Power Amplifier ZigBee Repeater (RoHS)
ZB-2550 CR	RS-485/RS-232 to ZigBee Converter (Host) (RoHS)
ZB-2550P CR	RS-485/RS-232 to High Power Amplifier ZigBee Converter (Host) (RoHS)
ZB-2570 CR	Ethernet/RS-485/RS-232 to ZigBee Converter (Host) (RoHS)
ZB-2570P CR	Ethernet/RS-485/RS-232 to High Power Amplifier ZigBee Converter (Host) (RoHS)