How to confirm the firmware version?

Steps to get the firmware version:

Step 1: Open the cover of GW-7553

Step 2: Close the initial pin 2, 3 (JP1) and flash protection pin 1, 2 (JP2) by jumper



Step 3: Connect the power supply



Step 4: Connect the PC and the GW-7553 by Com Port (RS-232)



Step 5: Turn the power on

Step 6: Run MiniOS7 utility on the PC (You can download MiniOS7 Utility at

http://ftp.icpdas.com.tw/pub/cd/8000cd/napdos/minios7/utility/minios7_utility/_.)

Step 7: Connect MiniOS7 Utility and the GW-7553 by click the connection button.

🚵 MiniOS7 Utility Verion 3.2.1											
Look in: 🛅 MiniOS7_Utility	💌 O 🌶 🖻	Lock in: Disk A		B							
Name Size Din FIRMWARE OS JMAGE TI68eu.F4 TI68eu.F4 1KB Tojdas 1KB MinIOS7_Utility.chm 1,015KB MinIOS7_Utility.chm 1,015KB MinIOS7_Utility.chm 1,015KB Junins000.dat 10KB Junins000.exe 679KB	Type Modified File Folder 2009/12/1 上午 11:03 File Folder 2009/12/1 上午 11:03 File Folder 2009/12/1 上午 11:03 F4 File 2008/12/1 上午 11:03 F4 File 2008/12/1 上午 11:03 F4 File 2008/12/1 上午 11:03 F4 File 2008/4/16 T午 11:55 網路設式 Connection 應用程言 Connection 医應用程言 Connection DAT File Baud Rate: [115200 ♥ Data Bit 8 ♥ Parity: [[None] ♥ Stop Bit [1 DK Cancel	No Name Image: Description of the system Image: Description of the system Image: Description of the system Image: Description of the system Image: Description of the system Image: Description of the system Image: Description of the system Image: Description of the system Image: Description of the system Image: Description of the system Image: Description of the system Image: Description of the system	5	ze Modiied							
Connection(F2) 🗊 Upload(F5) 💐 DiskTo	ool(F6) 🔝 Info(F7) 😰 Delete(F8) 🦪 Refresh(F9) 📇 Console(F10) 🔤 DOS	(F11) 🏟 Search(F12)								

Step 8: Get the firmware version

A MI-1087 TAUL V-1-2 9 1		-								
: 🖓 Fue 🍺 Connection 👻 🕼 Command 😰 Configuration 📑 10015 🤓 Help 🔹										
Look in: 🛅 MiniOS7_Utility	🔽 🔇 🤌 📂		:	Lock in: Disk A	•	~	256,393 bytes available	ti and the second s		
Name Size	Туре	Modified	No	Name			Size	Modified		
🛅 bin	File Folder	2009/12/1上午 11:03	0	7553v12.exe	э		202,252	2009/9/10上午 09:00:00		
E FIRMWARE	File Folder	2009/12/1 上午 11:03	1	autoexec.ba	ıt		11	2009/9/10上午 09:00:00		
	File Folder	2009/12/1 上午 11:03								
1KB	F4 File	2008/4/16 下午 11:55								
Cicpdas 1KB	網際網路建徑	2009/12/1 上午 11:03								
	應用程式擴充	2007/1/31 14 12:52								
MiniUS7_Utility.cnm 1,UISKB	□編譯的 HIML Hel 座田和→	2009/10/15 上十 09:								
MiniUS7_Utility.exe 2,206KB	應用性助 (1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(2009/11/9 1 + 02:18								
Ninios7_00iiy.ini IKB	祖恩武仁順 唯田君式擁容	2003/12/1 11 〒 01:36								
lunins000 dat 10KB	NE/THEPODE/C	2000/12/0 上午 10:07								
ie unins000.adt rottb ie unins000 exe 679KB	産用程式	2009/12/1上午11:03								
	2007131E.0-0									
<		>								
i7186EX>COM1, 2 files(s) 202,263 bytes										
🕞 Connection(F2) 🗐 Upload(F5) 😹 DiskTo	ool(F6) 📑 Info(F7) 🔞	Delete(F8) 🛃 Refresh	F9) 🚝	Console(F10)	🔤 DOS(F11)	ġā	Search(F12)			

7553v12.exe is the firmware name of GW-7553 in this example.

It means the firmware version is 1.2

Step 9: Turn the power off

Step 10: Close the initial pin 2, 3 (JP1) and flash protection pin 1, 2 (JP2) by jumper



Step 11: Close the cover of GW-7553