

# Related Products

# 5



## Power Supplies

▶▶▶ DR-120-24 *NEW*  
DR-120-48 *NEW*



### Specifications

Models	DR-120-24	DR-120-48
<b>Input</b>		
Range	88 AC ~ 264 AC	
Frequency	47 Hz ~ 63 Hz	
<b>Output</b>		
Power	24 Vdc/5.0 A max., 120 W	48 Vdc/2.5 A max., 120 W
<b>Mechanical</b>		
Dimensions (W x H x D)	65 mm x 125 mm x 100 mm	
Installation	DIN-Rail Mounting	
<b>Environmental</b>		
Operating Temperature	-10 °C ~ +60 °C	
Storage Temperature	-20 °C ~ +85 °C	-25 °C ~ +85 °C



DR-120-48 DR-120-24

▶▶▶ MDR-20-24 *NEW*  
MDR-60-24 *NEW*  
MDR-60-48 *NEW*



### Specifications

Models	MDR-20-24	MDR-60-24	MDR-60-48
<b>Input</b>			
Range	100 AC ~ 250 AC		
Frequency	50 Hz ~ 60 Hz		
<b>Output</b>			
Power	24 Vdc/1 A max., 24 W	24 Vdc/2.5 A max., 60 W	48 Vdc/1.25 A max., 60 W
<b>Mechanical</b>			
Dimensions (W x H x D)	22.5 mm x 90 mm x 100 mm	40 mm x 90 mm x 100 mm	40 mm x 90 mm x 100 mm
Installation	DIN-Rail Mounting		
<b>Environmental</b>			
Operating Temperature	-20 °C ~ +70 °C		
Storage Temperature	-20 °C ~ +85 °C		



MDR-60-24/  
MDR-60-48 MDR-20-24

▶▶▶ KA-52F/DIN-KA52F *NEW*  
KA52F-48/DIN-KA52F-48 *NEW*



### Specifications

Models	KA-52F	DIN-KA52F	KA-52F-48	DIN-KA52F-48
<b>Input</b>				
Range	100 AC ~ 250 AC			
Frequency	50 Hz ~ 60 Hz			
<b>Output</b>				
Power	24 Vdc/1.04 A max., 25 W		48 Vdc/0.52 A max., 25 W	
<b>Mechanical</b>				
Dimensions (W x H x D, Unit: mm)	54 x 36 x 93	68 x 50 x 107	54 x 36 x 93	68 x 50 x 107
Installation	No-mounting	DIN-Rail Mounting	No-mounting	DIN-Rail Mounting
<b>Environmental</b>				
Operating Temperature	0 °C ~ +50 °C			
Storage Temperature	-20 °C ~ +85 °C			



KA-52F/DIN-KA52F-48



DIN-KA52F/DIN-KA52F-48

▶▶▶ **GPSU06U-6** *NEW*  
**GPSU06E-6** *NEW*



**Specifications**

<b>Input</b>	
Range	100 V <sub>AC</sub> ~ 240 V <sub>AC</sub> OR 127 V <sub>DC</sub> ~ 370 V <sub>DC</sub>
Frequency	50 Hz ~ 60 Hz
<b>Output</b>	
Power	24 V <sub>DC</sub> /0.25 A max., 6 W
<b>Mechanical</b>	
Dimensions (W x H x D)	32 mm x 66 mm x 68 mm
Installation	No-mounting
<b>Environmental</b>	
Operating Temperature	0 °C ~ +40 °C
Storage Temperature	-20 °C ~ +85 °C



GPSU06U-6



GPSU06E-6  
(2 pole EURO plug)

**Stainless 35 mm DIN-Rail**

▶▶▶ **DRS-125**  
**DRS-240**  
**DRS-360**



<b>Material</b>	stainless sos304-1.0t
-----------------	-----------------------

**Ordering Information**

DRS-125	125 mm length, Stainless 35 mm DIN-Rail
DRS-240	240 mm length, Stainless 35 mm DIN-Rail
DRS-360	360 mm length, Stainless 35 mm DIN-Rail

**19" Rack Mounting Kit 3U**

▶▶▶ **RK-3UD-R**



<b>Dimensions</b>	
<p>Left Side View</p>	<p>Front View</p>




**Ordering Information**

RK-3UD-R	19" Rack Mounting Kit 3U
----------	--------------------------

## Cable

### ▶▶▶ CA-090510

#### Pin Assignments



#### RJ-45 8-Pin to DB-9 cable

The wiring diagram for a CA-090510 cable is shown in Table.

RJ-45		DB-9
Pin 1	↔	Pin 6
Pin 2	↔	Pin 7
Pin 3	↔	Pin 5
Pin 4	↔	Pin 2
Pin 5	↔	Pin 3



#### Ordering Information

CA-090510	9-Pin Female D-Sub & RJ-45 Cable, 1 m
-----------	---------------------------------------

## Industrial Enclosures

### ▶▶▶ I-950-ENC I-951-ENC



#### Specifications

Models	I-950-ENC	I-951-ENC
<b>Includes</b>		
Case Accessory		
2 x Polyamide cable glands		
4 x captive lid screws		
1 x DIN-Rail Mounting (20 cm)		
<b>Mechanical</b>		
<b>Casing</b>	Plastic	
<b>Dimensions (W x H x D)</b>	254 mm x 180 mm x 90 mm	254 mm x 180 mm x 111 mm
<b>Environmental</b>		
<b>Temperature</b>	0 °C ~ +50 °C for Protection rating IP66	



I-950-ENC



I-951-ENC

#### Ordering Information

I-950-ENC CR	Industrial Enclosure (254 mm x 180 mm x 90 mm) (RoHS)
I-951-ENC CR	Industrial Enclosure (254 mm x 180 mm x 111 mm) (RoHS)

### ▶▶▶ I-3625-ENC



#### Specifications

<b>Includes</b>		
Case Accessory		
2 x Polyamide cable glands		
6 x captive lid screws		
1 x DIN-Rail Mounting (35.8 cm)		
<b>Mechanical</b>		
<b>Casing</b>	Plastic	
<b>Dimensions (W x H x D)</b>	360 mm x 254 mm x 165 mm	
<b>Environmental</b>		
<b>Temperature</b>	0 °C ~ +50 °C for Protection rating IP66	



I-3625-ENC

#### Ordering Information

I-3625-ENC CR	Industrial Enclosure (RoHS)
---------------	-----------------------------

# ICP DAS Catalogs

## Compact PAC Products Catalog

- XP-8000-Atom Series
- XP-8000 Series
- WP-8000 Series
- LP-8000 Series
- iP-8000 Series
- ViewPAC Series
- MotionPAC Series
- I/O Expansion Units
- I/O Modules
- 7188/7186 Series
- 5000 Series



## Industrial Remote I/O Products Catalog

- RS-485 Remote I/O Modules
- Ethernet Remote I/O Modules
- FRnet I/O Modules
- CAN bus Remote I/O Modules
- PROFIBUS Remote I/O Modules



## Touch HMI Devices Brochure

- 2.8" high-color LCD touch screen
- 3.5" high-color LCD touch screen
- 4.3" high-color LCD touch screen
- RS-232, RS-485 or Ethernet Interface
- HMIWorks development software
- Modbus TCP, Modbus RTU and DCON protocols
- Standard C or Ladder programming




## Industrial Data Acquisition for ISA and PCI Bus Full Catalog

- Multi-port Serial Communication Boards
- CAN bus Communication Boards
- PCI/ISA Data Acquisition and I/O Boards
- PCI bus Battery-Backup Memory Boards
- Daughter Boards & Accessories
- Motion Control & Watchdog Boards
- Signal Conditioning & Power Modules
- FRnet Remote I/O Products
- LED Display



## Industrial Communication & Networking Products Catalog

- Multi-port Serial Communication Boards
- Programmable Serial-to-Ethernet Device Servers with PoE or LAN Switch
- Programmable Serial-to-Fiber Device Servers
- Modbus TCP to RTU/ASCII Gateway
- Addressable RS-232 to RS-485 Converter
- RS-232/422/485 Converter, Repeater and HUB



## New Members in I/O Cards Short Form

- PCI Express Cards
- Universal PCI Cards
- Analog Input and Output Cards
- Digital Input and Output Cards
- Multi-port Serial Cards



## Fieldbus Solutions Full Catalog

- CAN bus Communication Products
- CANopen Communication Products
- DeviceNet Communication Products
- J1939 Communication Products
- PROFIBUS Communication Products
- HART Communication Products
- Ethernet/IP Communication Products
- BACnet Communication Products



## Industrial Wireless Communication Products

- Industrial Wireless Series
- DSSS RF Modems
- 2G/3G Mini-PAC/Modules/Modems
- ZigBee Converters & I/O Modules
- GPS Solutions



## Industrial CAN bus Products Catalog

- CAN Converters, CAN Repeater, CAN Bridge, CAN Switch, CAN Cards, Surge Protector, PACs, CAN Expansion Modules, CAN Power Meters, CAN Connector, CAN Transformation Cable
- CANopen Gateways, CANopen Master Interfaces, CANopen Remote I/O Modules
- DeviceNet Gateways, DeviceNet Master Interfaces, DeviceNet Remote I/O Modules
- J1939 Gateways



## M2M Total Solutions

- 2G/3G Solutions
- WLAN Solutions
- Remote Maintenance Solutions
- DSSS RF/GPS Solutions
- M2M Series Selection Guide





## ICP DAS CO., LTD.

### Taiwan (Headquarters)

Website: <http://www.icpdas.com>

E-mail: [sales@icpdas.com](mailto:sales@icpdas.com)

TEL: +886-3-597-3366

FAX: +886-3-597-3733

### China

Website: <http://www.icpdas.com.cn>

E-mail: [sales\\_sh@icpdas.com.cn](mailto:sales_sh@icpdas.com.cn)

TEL: +86-21-6247-1722

FAX: +86-21-6247-1725

### Europe

Website: <http://www.icpdas-europe.com>

E-mail: [info@icpdas-europe.com](mailto:info@icpdas-europe.com)

TEL: +49(0)7121-14324-0

FAX: +49(0)7121-14324-90

### USA

Website: <http://www.icpdas-usa.com>

E-mail: [sales@icpdas-usa.com](mailto:sales@icpdas-usa.com)

TEL: +1-310-517-9888

FAX: +1-310-517-0998

## Local Distributor

