











Ordering Information

PCI-P8R8U CR	Universal PCI, 8-ch Isolated DI and 8-ch Relay Output Board (RoHS) Includes one CA-4002 D-Sub connector
PCI-P16R16U CR	Universal PCI, 16-ch isolated DI and 16-ch Relay Output (RoHS) Includes one CA-4037W cable and two CA-4002 D-Sub connectors

Accessories

	CA-3710 CR	DB-37 Male-Male D-sub cable 1 M (Cable for Daughter Board (45°)) (RoHS)
	CA-3710D CR	DB-37 Male-Male D-sub cable 1 M (Cable for Daughter Board (180°)) (RoHS)
	CA-3715DM-H CR	DB-37 Male-Male Cable, 1.5 M, 180° (RoHS)
	CA-3730DM-H CR	DB-37 Male-Male Cable, 3.0 M, 180° (RoHS)
	CA-3750DM CR	DB-37 Male-Male Cable, 5.0 M, 180° (RoHS)
	CA-3750DM-H CR	DB-37 Male-Male Cable, 5.0 M, 180° (RoHS)
	CA-4002 CR	37-pin Male D-sub connector with plastic cover (RoHS)
	CA-4037W CR	40-pin flat & D-sub 37-pin Female cable 24 cm (RoHS)
	DB-37 CR	Directly connect signal to D-sub 37-pin connector (RoHS)
	DN-37 CR	DIN Rail Mounting 37-pin Connector (RoHS)

