
X503 Release Note:


Supported Products:

I-7188XB/XG/EX/EG, μ PAC-7186EX/EG/EX-FD/EX-SM, μ PAC-7186PEX

Specifications:

Serial Port	
Number of port	RS-232 x 1
Interface	TxD, RxD, RTS, CTS, GND
Controller	16C550 compatible
	Speed: 115200 bps Max.
	Data bit : 5, 6, 7, 8
	Stop bit : 1, 1.5, 2
	Parity : None, Even, Odd, Mark, Space
	FIFO: Internal 16 bytes for each port
Intra-module Isolation, Field to Logic	non-isolated

Pin Assignment:



Programming:

for I-7188XB

http://ftp.icpdas.com/pub/cd/8000cd/napdos/7188xabc/7188XB/Demo/BC_TC/Xboard/

for I-7188EX

http://ftp.icpdas.com/pub/cd/8000cd/napdos/7188e/demo/bc_tc/xboard/

for μ PAC-7186EX

http://ftp.icpdas.com/pub/cd/8000cd/napdos/7186e/demo/basic/bc_tc/xboard/

for I-7188XG/I-7188EG (manual, Driver, Demo)

<http://ftp.icpdas.com/pub/cd/8000cd/napdos/isagraf/>

Manual:

<http://ftp.icpdas.com/pub/cd/8000cd/napdos/xboard/document/>

Technical Service:

service@icpdas.com