

X507

1-Port RS-422/485, 4-channel D/I and 4-channel D/O

Features

- 1-Port Non-Isolation RS-422/485 and 4-channel Non-Isolation Digital Input and 4-channel Non-Isolation Digital Output



Introduction

The X-board series are for I-7188XA, I-7188XB, I-7188XC, I-7188XG, I-7188EG, I-7188EX and uPAC-7186EX Series (uPAC-7186EX, uPAC-7186PEX, uPAC-7186EG, uPAC-7186EX-FD, uPAC-7186EX-SM).


Above one μ PAC can plug only one X-board.

X507 is a 1-Port Non-Isolation RS-422/485 and 4-channel Non-Isolation Digital Input and 4-channel Non-Isolation Digital Output X-board for I-7188XB, I-7188XG, I-7188EX, I-7188EG and uPAC-7186EX Series.

Specifications

COM Ports	
Ports	1 x RS-422 (TxD+, TxD-, RxD+, RxD-) 1 x RS-485 (TxD+, TxD-)
Baud Rate	115200 bps Max. 1200 ~ 115200 bps 10 k, 20 k, 50 k, 125 k, 250 kbps, 500 k, 800 k, 1M 125 k, 250 k, 500 k
FIFO Size	16 bytes
Mechanical	
Dimensions (mm)	38 mm x 64 mm
Environmental	
Operating Temperature	-25 ~ +75 °C
Storage Temperature	-40 ~ +80 °C
Humidity	5 ~ 90 %, Non-condensing

Pin Assignments



Ordering Information

X507 CR	1-Port RS-422/485, 4-channel D/I and 4-channel D/O (RoHS)
----------------	---