



X561

64 MB Flash with 3-port RS-232 (5-Pin)

Features

- 64 MB Flash with 3-Port Non-Isolation 5-wire RS-232



Introduction

The X-board series are for I-7188XA, I-7188XB, I-7188XC, I-7188XG, I-7188EG, I-7188EX and uPAC-7186EX Series (uPAC-7186EX, uPAC-7186PEX, uPAC-7186EG, uPAC-7186EX-FD, uPAC-7186EX-SM).

Above one μ PAC can plug only one X-board.

X561 is a 64 MB Flash with 3-Port Non-Isolation 5-wire RS-232 X-board for I-7188XA, I-7188XB, I-7188XG, I-7188EX, I-7188EG and uPAC-7186EX Series. (Without Case)

Specifications

Memory	
Type	Flash
Size	64 Mbytes
COM Ports	
Ports	3 x 3-wire RS-232 (TxD, RxD, GND)
Baud Rate	115200 bps Max. 1200 ~ 115200 bps 10 k, 20 k, 50 k, 125 k, 250 kbps, 500 k, 800 k, 1M 125 k, 250 k, 500 k
FIFO Size	16 bytes
Mechanical	
Dimensions (mm)	68 mm x 64 mm
Environmental	
Operating Temperature	-25 ~ +75 °C
Storage Temperature	-40 ~ +80 °C
Humidity	5 ~ 90 %, Non-condensing

Ordering Information

X561 CR	64 MB Flash with 3-port RS-232 (5-Pin) (RoHS)
----------------	---