



## PCI-1802LU

Universal PCI, 330kS/s, 32-ch, 12-bit AI Multifunction Board

## PCI-1802HU

Universal PCI, 44k S/s, 32-ch, 12-bit AI Multifunction Board

### Features

- Universal PCI (3.3 V/5 V) Interface
- Supports Card ID (SMD Switch)
- 2-channel, 12-bit Analog Output
- 16-channel 5 V/TTL Digital Output
- 16-channel 5 V/TTL Digital Input
  - Pull-high and Pull-low Resistors for DI Channels
- 32 Single-ended/16 Differential Analog Input Channels
  - 12-bit, 330 kS/s or 44 kS/s AD Converter
  - Built-in MagicScan Controller
  - Internal Trigger: Software-trigger, Pacer-trigger
  - External Trigger: Post-trigger, Pre-trigger, Middle-trigger
- High-speed data transfer rate up to 2.7 M words/sec.



### Introduction

The PCI-1802LU/HU card is designed as an easy replacement for the PCI-1802L/H without requiring any modification to the software or the driver.

The PCI-1802LU/HU is a high-performance multifunction card that provides high-speed Analog and Digital I/O functions. The PCI-1802LU/HU is based on the Universal PCI interface, supporting both the 3.3 V and the 5 V PCI bus, and features a continuous 330 kS/s or 44 kS/s 12-bit resolution AD converter, an 8 K-sample hardware FIFO, a MagicScan controller (for multi-channel scanning), a 2-channel 12-bit DA converter, and 16-channel Digital Input and 16-channel Digital Output.

The PCI-1802LU/HU provides either 32-channel single-ended or 16-channel differential Analog Inputs that are jumper selectable, and a programmable high-speed PGA that is equipped for gain controls (0.5/1/2/4/8 for Low Gain, and 0.5/1/5/10/50/100/500/1000 for High Gain).

The PCI-1802LU/HU also includes an onboard Card ID switch and pull-high/low DI resistors. The Card ID enables the board to be recognized via software if two or more PCI-1802LU/HU cards are installed in the same computer. The pull-high/pull-low resistors allow the DI status to be predefined instead of remaining floating if the DI channels are disconnected or interrupted.

### Pin Assignments

Pin Assignment	Terminal No.	Pin Assignment	Pin Assignment	Terminal No.	Pin Assignment
AI_0	01	20 AI_16	DO 0	01	02 DO 1
AI_1	02	21 AI_17	DO 2	03	04 DO 3
AI_2	03	22 AI_18	DO 4	05	06 DO 5
AI_3	04	23 AI_19	DO 6	07	08 DO 7
AI_4	05	24 AI_20	DO 8	09	10 DO 9
AI_5	06	25 AI_21	DO 10	10	12 DO 11
AI_6	07	26 AI_22	DO 12	12	14 DO 13
AI_7	08	27 AI_23	DO 14	14	16 DO 15
AI_8	09	28 AI_24	GND	16	18 GND
AI_9	10	29 AI_25	+5 V	18	20 +12 V
AI_10	11	30 AI_26	CON1		
AI_11	12	31 AI_27	Pin Assignment	Terminal No.	Pin Assignment
AI_12	13	32 AI_28	DI 0	01	02 DI 1
AI_13	14	33 AI_29	DI 2	03	04 DI 3
AI_14	15	34 AI_30	DI 4	05	06 DI 5
AI_15	16	35 AI_31	DI 6	07	08 DI 7
A.GND	17	36 Da2 out	DI 8	09	10 DI 9
Da1 out	18	37 D.GND	DI 10	11	12 DI 11
Ext_Trg	19		DI 12	13	14 DI 13
			DI 14	15	16 DI 15
			GND	17	18 GND
			+5 V	19	20 +12 V
			CON2		

### Software

#### Drivers

- 32/64-bit Windows 10/11
- Linux  DASyLab

#### Sample Programs

- DOS Lib and TC/BC/MSC Demo
- VB/VC/Delphi/VB.NET/C#.NET/VC.NET/LabVIEW/Python/MATLAB

### Applications

- High speed data acquisition system
- Process monitor and control.
- Vibration analysis.

















### Ordering Information

<b>PCI-1802LU CR</b>	Universal PCI, 330kS/s, 32-ch, 12-bit AI Multifunction Board (RoHS) Includes one CA-4002 D-Sub connector
<b>PCI-1802HU CR</b>	Universal PCI, 44k S/s, 32-ch, 12-bit AI Multifunction Board (RoHS) Includes one CA-4002 D-Sub connector

## Hardware Specifications

Model	PCI-1802LU	PCI-1802HU
<b>Hardware</b>		
Card ID	Yes (4-bit)	
Connector	Female DB37 x 1 , Male 20-bit ribbon x 2	
<b>Analog Input</b>		
Channels	32 single-ended/16 differential	
Range	Gain: 0.5, 1, 5, 10, 50, 100, 500, 1000 Bipolar Range: $\pm 10$ V, $\pm 5$ V, $\pm 1$ V, $\pm 0.5$ V, $\pm 0.1$ V, $\pm 0.05$ V, $\pm 0.01$ V, $\pm 0.005$ V Unipolar Range: 0 ~ 10 V, 0 ~ 1 V, 0 ~ 0.1 V, 0 ~ 0.01 V	
Resolution	12-bit	
Accuracy	0.01% of FSR $\pm 1$ LSB @ 25 °C, $\pm 10$ V	
Sampling Rate	330 kS/s. Max.	44 kS/s. Max.
Input Impedance	10 M $\Omega$ /6 pF	
Overvoltage Protection	Continuous $\pm 35$ Vp-p	
Zero Drift	$\pm 2$ ppm/°C of FSR	
FIFO Size	8192 samples	
Trigger Mode	Software, Internal programmable pacer, External (5 V/TTL)	
Data Transfer	Polling	
<b>Analog Output</b>		
Channels	2	
Range	Bipolar: $\pm 5$ V, $\pm 10$ V	
Resolution	12-bit	
Accuracy	0.06% of FSR $\pm 1$ LSB @ 25 °C, $\pm 10$ V	
Response Time	1.0 MHz (Typical)	
Voltage Output Capability	$\pm 5$ mA	
Slew Rate	8.33 V/ $\mu$ s	
Operation Mode	Static Update	
<b>Digital Input</b>		
Channels	16	
Type	5 V/TTL	
ON Voltage Level	2.0 V Min.	
OFF Voltage Level	0.8 V Max.	
Response Speed	1.0 MHz (Typical)	
Trigger Mode	Static Update	
<b>Digital Output</b>		
Channels	16	
Type	5 V/TTL	
Operation Mode	Static Update	
Load Voltage	Logic 0: 0.4 V Max. , Logic 1: 2.4 V Min.	
Load Current	Sink: 2.4 mA @ 0.8 V , Source: 0.8 mA @ 2.0 V	
Response Speed	1.0 MHz (Typical)	
<b>Timer/Counter/Frequency</b>		
Channels	3 (Independent x 1/Internal pacer x 1/External pacer x 1)	
Type	5 V/TTL	
Resolution	16-bit	
Input Frequency	10 MHz Max.	
Reference Clock	Internal: 8 MHz	
<b>PC Bus</b>		
Type	3.3 V/5 V Universal PCI , 32-bit, 33 MHz	
Data Bus	16-bit	
<b>Power</b>		
Consumption	300 mA @ +5 V	
<b>Mechanical</b>		
Dimensions (mm)	105 x 200 x 22 (W x L x D)	
<b>Environment</b>		
Operating Temperature	0 ~ +60°C	
Storage Temperature	-20 ~ +70°C	
Humidity	5 ~ 85% RH, Non-condensing	

## Accessories

	CA-2002 CR	20-pin flat cable, 20 cm x 2 (RoHS)
	CA-2010 CR	20-pin flat cable, 1 M (RoHS)
	CA-2020 CR	20-pin flat cable, 2 M (RoHS)
	CA-3710 CR	DB-37 Male-Male D-sub cable 1 M (Cable for Daughter Board (45°)) (RoHS)
	CA-3710D CR	DB-37 Male-Male D-sub cable 1 M (Cable for Daughter Board (180°)) (RoHS)
	CA-3715DM-H CR	DB-37 Male-Male Cable, 1.5 M, 180° (RoHS)
	CA-3730DM-H CR	DB-37 Male-Male Cable, 3.0 M, 180° (RoHS)
	CA-4002 CR	37-pin Male D-sub connector with plastic cover (RoHS)
	DB-1825 CR	Analog Input Screw terminal Board (RoHS)
	DB-8225 CR	Screw terminal board , filter circuitry can be added for 1800HU, 1800LU (RoHS)
	DB-889D CR	16-channel Analog Multiplexer Board (for PCI-1800LU/HU) (RoHS)
	DB-16P CR	16-channel Isolated Digital Input Daughter Board (RoHS)
	DB-16R CR	16-channel Relay Output Daughter Board (RoHS)
	DN-37 CR	DIN Rail Mounting 37-pin Connector (RoHS)
	DN-20/DN-20-381 CR	20-pin DIN-RAIL mounting I/O connector board (RoHS)
	2AB125R CR	Resistor DIP 125R 0.1% 1/4W MF 50PPM (1PCS) (RoHS)

### PCI-1802HU/PCI-1802LU PCI-1800HU/PCI-1800LU

